

Wall Covering

Spray Adhesive



<0.0g/ml VOC adhesive
for approved Wall
Coverings and other
applications



1500



PRODUCT CHARACTERISTICS

Spray-Lock® 1500 Wall Covering Spray Adhesive bonds approved wall coverings for commercial and residential applications. Coverings must be structurally sound with non-grooved backing for use in commercial or residential applications.

Spray-Lock® 1500 uses 60% less adhesive than traditional trowel-on adhesives.

Spray-Lock® 1500 increases productivity with a faster application rate, saving you time and money. Spray-Lock® 1500 comes in easy to use aerosol cans.

ADVANTAGES

- <0.0g/ml VOC content
- Non-Toxic, water-based adhesive
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistance
- No telegraphing behind sheets
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® 1500 Adhesive adheres Approved Wall Coverings onto the following properly prepared smooth substrates:

- Dry Wall / Sheet Rock / Plaster sheet
- Backer Board / Plywood Sheet
- Wood
- Metal

NOTE: These surfaces MUST be primed before adhesive is applied. These surfaces must be DUST FREE before adhesive is applied and kept DUST FREE while adhesive is drying before application of Wall Covering.

Please refer to the Wall Preparation Guide for detailed instruction on substrate conditioning before installation.

TECHNICAL CHARACTERISTICS

Spray-Lock® 1500's formula is a water based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

Spray-Lock® 1500 adhesive is solvent free, emits no harmful fumes and contains <0.0g/ml VOC (**Volatile Organic Compounds**) content. According to EPA Method 8260B.

Spray-Lock® 1500 uses a safe non ozone depleting HFC propellant.

TECHNICAL DATA

Chemical Type	Water-based Acrylic Blend
Appearance	Milky white frost bubbles
Odor	Sweet mild odor
Flash point	Will not burn
NFPA 704 Flammability Rating	0 (Non Flammable)
Storage:	Do not subject to freezing temperatures.
Shelf life	3 years if unopened
Open time:	2 hours
Dry time:	Once adhesive is dry to touch (10-20 minutes)
VOC content	<0.0g/ml calculated



STANDARD AEROSOL

Shake aerosol can well. Snap blue tab on top of trigger to activate the can, aim at desired substrate. Pull blue lever to spray adhesive.

COVERAGE GUIDE - STANDARD AEROSOL

	OVER PLYWOOD - STANDARD AEROSOL	OVER DENS SHIELD & DRYWALL
APPROVED WALL COVERING	50-60 ft ² / 4.6-5.5 m ²	60-70 ft ² / 5.5-6.5 m ²

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented.

Please refer to Installation Guidelines for detailed instructions