

Approved Luxury Vinyl Tile Luxury Vinyl Plank Carpet Tile

Spray Adhesive

<0.0g/ml VOC adhesive for installation of LVT / LVP /
Carpet Tile.



6500 Platinum

PRODUCT CHARACTERISTICS

Spray-Lock® 6500 Platinum is a versatile spray adhesive naturally suited for adhering approved LVT and LVP in commercial and residential applications.

Spray-Lock® 6500 Platinum uses 80% less adhesive compared to trowel applied bucket adhesive. Spray-Lock's® instant shear strength allows for all traffic with out any adhesive indentation, displacement or movement associated with heavy weight bearing loads.

Spray-Lock® 6500 Platinum is a non-toxic, <0.0g/ml VOC product that allows you to occupy your space as soon as installation has been completed.

ADVANTAGES

- Use 80% less adhesive
- Allows all traffic immediately (including hospital beds)
- <0.0g/ml VOC content
- Non-Toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistance
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® 6500 Platinum bonds approved LVT / LVP to the following properly prepared smooth, flat, dust free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

TECHNICAL CHARACTERISTICS

- **Spray-Lock® 6500 Platinum** provides immediate sheer strength after installation allowing instant access to finished floor.
- **Spray-Lock® 6500 Platinum** is solvent free, emits no harmful fumes and contains <0.0g/ml VOC's (Volatile Organic Compounds) content. According to EPA test method 8260B.
- **Spray-Lock® 6500 Platinum** uses a non-ozone depleting HFC propellant.
- **Spray-Lock® 6500 Platinum** withstands 10 lbs. of vapor emissions / 93% RH and 12pH.

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

TECHNICAL DATA

Chemical Type	Water-based Acrylic Blend
Appearance	Milky white frost bubbles
Odor	Sweet mild odor
Flash point	Will not burn
NFPA 704 Flammability Rating	0 (Non Flammable)
Storage:	Do not subject to freezing temperatures.
Shelf life	3 years if unopened.
Open time:	4 hours
Dry time:	Once adhesive is dry to touch (10-20 minutes)
VOC content	<0.0g/ml calculated
Foot traffic allowance	Immediate
Heavy machinery allowance	Immediate
Resistance to moisture (Regular)	Excellent: 10 lbs. / 1000 sq. ft. or 93% RH / 12pH
Underfloor heating systems	Yes



THE UPSIDE-DOWN AEROSOL WITH LEVER
 Slide lever prongs underneath valve collar, point tip towards substrate. Press lever to spray adhesive. This option is perfect for all sized jobs. Cutting in is simple and most importantly it keeps the installer standing upright.

COVERAGE GUIDE

	UPSIDE DOWN AEROSOL
LVT / LVP (STANDARD)	100-125 sq. ft.