

VCT

Vinyl Composition Tile Spray Adhesive

<0.0g/ml VOC adhesive for installation of
Vinyl Composition Tile.



9500



EPA TEST METHOD 8260B



PRODUCT CHARACTERISTICS

Spray-Lock® 9500 is a versatile spray adhesive naturally suited for adhering vinyl composition tile (VCT) in commercial and residential applications.

Spray-Lock® 9500 uses 80% less adhesive compared to trowel applied bucket adhesive. Spray-Lock's® instant shear strength allows for all traffic with out any adhesive indentation, displacement, or movement associated with heavy weight bearing loads.

Spray-Lock® 9500 is a non-toxic, <0.0g/ml VOC product that allows you to occupy your space as soon as installation has been completed.

ADVANTAGES

- Use 80% less adhesive
- Allow all traffic immediately (including hospital beds)
- **<0.0g/ml VOC content**
- Non-Toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistance
- No offensive odors
- No trowel marks

SUITABLE SUBSTRATES

Spray-Lock® 9500 bonds vinyl composition tile (VCT) to the following properly prepared smooth, flat, dust free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

DO NOT USE FORMULA 6500 FOR VINYL COMPOSITION TILE.

TECHNICAL CHARACTERISTICS

- **Spray-Lock® 9500** provides immediate shear strength after installation allowing immediate access to finished floor.
- **Spray-Lock® 9500** is solvent free, emits no harmful fumes and contains **<0.0g/ml VOC** (Volatile Organic Compounds) content. According to EPA test method 8260B.
- **Spray-Lock® 9500** uses a non-ozone depleting HFC propellant.
- **Spray-Lock® 9500** withstands 8 lbs. of vapor emissions/ 90% RH and 11 pH.

TECHNICAL DATA

Chemical Type	Water-based Acrylic Blend
Appearance	Extra small milky white frost bubbles
Odor	Sweet mild odor
Flash point	Will not burn
NFPA 704 Flammability Rating	0 (Non Flammable)
Storage:	Do not subject cylinders or aerosols to freezing temperatures.
Shelf life	3 years if unopened
Open time:	2 hours
Dry time:	Once adhesive is dry to touch (10-20 minutes)
VOC content	<0.0g/ml calculated
Foot traffic allowance	Immediate
Heavy machinery allowance	Immediate
Resistance to moisture (Regular)	Excellent: 8 lbs. / 1000 sq. ft. or 90% RH / 11pH
Underfloor heating systems	Yes



THE UPSIDE-DOWN AEROSOL WITH LEVER

Slide lever prongs underneath valve collar, point tip towards substrate. Press lever to spray adhesive. This option is perfect for all sized jobs. Cutting in is simple and most importantly it keeps the installer standing upright.

COVERAGE GUIDE

	UPSIDE DOWN AEROSOL
VINYL COMPOSITION TILE	170-200 sq. ft.