

VCT

Vinyl Composition Tile

Spray Adhesive

<0.0g/ml VOC adhesive for installation of Vinyl Composition Tile.



9500 Platinum

PRODUCT CHARACTERISTICS

Spray-Lock® 9500 Platinum is a versatile spray adhesive naturally suited for adhering vinyl composition tile (VCT) in commercial and residential application.

Spray-Lock® 9500 Platinum uses 80% less adhesive compared to trowel applied bucket adhesive. Spray-Lock's® instant shear strength allows for all traffic with out any adhesive indentation, displacement, or movement associated with heavy weight bearing loads.

Spray-Lock® 9500 Platinum is a non-toxic, <0.0g/ml VOC product that allows you to occupy your space as soon as installation has been completed.

ADVANTAGES

- Use 80% less adhesive
- Allow all traffic immediately
- <0.0g/ml VOC content
- Non-Toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistance
- No offensive odors
- No trowel marks

SUITABLE SUBSTRATES

Spray-Lock® 9500 Platinum bonds vinyl composition tile (VCT) to the following properly prepared smooth, flat, dust free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass

TECHNICAL CHARACTERISTICS

- **Spray-Lock® 9500 Platinum** provides immediate shear strength after installation allowing immediate access to finished floor.
- **Spray-Lock® 9500 Platinum** is solvent free, emits no harmful fumes and contains <0.0g/ml VOC's (Volatile Organic Compounds) content according to EPA test method 8260B.
- **Spray-Lock® 9500 Platinum** uses non-ozone depleting HFC propellant.
- **Spray-Lock® 9500 Platinum** withstands 10 lbs of vapor emissions, 93% RH and a 12 pH.

TECHNICAL DATA

Chemical Type	Water-based acrylic blend
Appearance	Milky white frost bubbles
Odor	Sweet, mild odor
Flash point	Will not burn
NFPA 704 Flammability Rating	0 (Non Flammable)
Storage	Store at a temperature range from 50°F - 120°F
Shelf life	3 years if unopened
Open time	2 hours
Dry time	Once adhesive is dry to touch (10-20 minutes)
VOC content	Less than 0.0 g/ml calculated
Foot traffic allowance	Immediate
Heavy machinery allowance	Immediate
Resistance to moisture (Regular)	Excellent: 10 lbs. per 1000 sq. ft. or 93% RH / 12pH
Underfloor heating systems	Yes



THE UPSIDE-DOWN AEROSOL WITH LEVER

Slide lever prongs underneath valve collar, point tip towards substrate. Press lever to spray adhesive. This option is perfect for all sized jobs. Cutting in is simple and most importantly it keeps the installer standing upright.

COVERAGE GUIDE

	UPSIDE DOWN AEROSOL
VINYL COMPOSITION TILE	170-190 ft ²