

Wall Tile

Spray Adhesive



<0.0g/ml VOC adhesive for approved Wall Tile and other applications



PRODUCT CHARACTERISTICS

Spray-Lock® WTA Wall Tile Spray Adhesive bonds approved wall tile for commercial and residential applications. Tiles must be structurally sound with non-grooved backing for use in commercial or residential applications.

Spray-Lock® WTA uses 60% less adhesive than traditional trowel-on adhesives.

Spray-Lock® WTA increases productivity with a faster application rate, saving you time and money. Spray-Lock® WTA comes in easy to use aerosol cans.

ADVANTAGES

- <0.0g/ml VOC content
- Non-Toxic, water-based adhesive
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistance
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® WTA adheres approved wall tile onto the following properly prepared smooth substrates:

- Dry Wall / Sheet Rock / Plaster sheet
- Backer Board / Plywood Sheet
- Wood
- Metal

NOTE: These surfaces MUST be primed before adhesive is applied. These surfaces must be DUST FREE before adhesive is applied and kept DUST FREE while adhesive is drying before application of the wall tile.

Please refer to the Wall Preparation Guide for detailed instruction on substrate conditioning before installation.

TECHNICAL CHARACTERISTICS

Spray-Lock® WTA's formula is a water based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

Spray-Lock® WTA is solvent free, emits no harmful fumes and contains <0.0g/ml VOC (Volatile Organic Compounds) content. According to EPA test method 8260B.

Spray-Lock® WTA uses a safe non ozone depleting HFC propellant.

TECHNICAL DATA

Chemical Type	Water-based Acrylic Blend
Appearance	Milky white frost bubbles
Odor	Sweet mild odor
Flash point	Will not burn
NFPA 704 Flammability Rating	0 (Non Flammable)
Storage:	Do not subject to freezing temperatures.
Shelf life	3 years if unopened
Open time:	1 hour
Dry time:	Once adhesive is dry to touch (10-20 minutes)
VOC content	<0.0g/ml calculated



STANDARD AEROSOL

Shake aerosol can well. Snap blue tab on top of trigger to activate the can, aim at desired substrate. Pull blue lever to spray adhesive.

COVERAGE GUIDE - STANDARD AEROSOL

	16 OZ. AEROSOL CAN	22 OZ. AEROSOL CAN
APPROVED WALL TILE	30-40 sq.ft. / 2.8-3.7 m ²	40-50 sq.ft. / 3.7-4.6 m ²

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented.

Please refer to Installation Guidelines for detailed instructions