

# Wall Panel

## Spray Adhesive



<0.0g/ml VOC adhesive for approved Wall Panel and other applications



# 1500

### PRODUCT CHARACTERISTICS

**Spray-Lock™ 1500** Wall Panel Spray Adhesive bonds approved wall panels for commercial and residential applications. Panels must be structurally sound with non-grooved backing for use in commercial or residential applications.

Spray-Lock™ 1500 uses 60% less adhesive than traditional trowel-on adhesives.

Spray-Lock™ 1500 increases productivity with a faster application rate, saving you time and money. Spray-Lock™ 1500 comes in easy to use aerosol cans.

### ADVANTAGES

- <0.0g/ml VOC content (Both content and emissions)
- Non-Toxic, water based adhesive
- Easy water cleanup while adhesive is still wet
- Non- flammable
- High moisture and pH resistance
- No telegraphing behind sheets

### SUITABLE SUBSTRATES

Spray-Lock 1500 Adhesive adheres Approved Wall Panel onto the following properly prepared smooth substrates:

- Dry Wall / Sheet Rock / Plaster sheet
- Backer Board / Plywood Sheet
- Wood
- Metal

**NOTE: These surfaces MUST be primed before adhesive is applied. These surfaces must be DUST FREE before adhesive is applied and kept DUST FREE while adhesive is drying before application of Wall Panel**

Please refer to the Wall Preparation Guide for detailed instruction on substrate conditioning before installation.

### TECHNICAL CHARACTERISTICS

**Spray-Lock 1500** Formula is a water based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

**Spray-Lock 1500** adhesive is solvent free, emits no harmful fumes and contains <0.0g/ml VOC (Volatile Organic Compounds) content or emissions thereafter.

**Spray-Lock 1500** uses only safe non ozone depleting HFC propellant.

## TECHNICAL DATA

Chemical Type	Water based acrylic blend
Appearance	Milky white frost bubbles
Odor	Sweet mild odor
Flash point	Will not burn
NFPA 704 Flammability Rating	0 (Non Flammable)
Storage:	Do not subject aerosols to freezing temperatures.
Shelf life	2 years if unopened
Open time:	1 hour
Dry time:	Once adhesive is dry to the touch (10-40 minutes)
VOC content	<0.0g/ml calculated



### STANDARD AEROSOL

Easy to use. Snap the top tab, give the can a shake and start spraying. The Aerosol can be used on multiple jobs and fits into your back pocket. Very simple operation and convenient.

## COVERAGE GUIDE - STANDARD AEROSOL

	OVER PLYWOOD -STANDARD AEROSOL	OVER DENS SHIELD & DRYWALL
APPROVED WALL PANEL	50-60 sq.ft/ 4.6-5.5 sq.m	60-70 sq.ft/ 5.5-6.5 sq.m

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented.

Please refer to Installation Guidelines for detailed instructions



